

E12

G16

OPAL G16 LED 75W EQUIVALENT



Ø 1 3/4"

PACKAGING



NOTE: Refer to image for scale/Se référer à l'image pour l'échelle

SPECIFICATIONS

WATTS	6
DELIVERED LUMENS	750
LAMP SHAPE	G16
GLASS SHADE	OPAL*
BASE / ANSI BASE	CANDELABRA / E12
MAXIMUM HEIGHT	3"
MAXIMUM DIAMETER	1 3/4"
CRI	80+
BEAM ANGLE	360°
JA8 CERTIFIED	NO
ENCLOSED RATED	YES
OPERATING TEMP.	-20° C TO 45° C
CASE QUANTITY	12/144
LIFE CYCLE @ 3 HRS/DAY	18 YEARS
ENERGY COST @10.65¢/kWh†	\$0.61 / YEAR
WARRANTY	5 YRS / 20,000 HRS

† Refers to Estimated annual cost

NEW

DESCRIPTION

ACTIVE CODE

SCHEDULED
SKU UPDATESCHEDULED
NEW CODE

3000 KELVIN · LUMENS 750

D40238A



4000 KELVIN · LUMENS 750

D40248A

*Opal/Frosted bulb SKUs may exhibit warmer colour temperatures than their Clear-glass counterparts and cannot be directly compared due to glass differences.

Dimmability Data / Données de gradation

- ✓ SMOOTH AND CONSISTENT DIMMING
- X NOT RECOMMENDED
- INCONSISTENT DIMMING TRANSITION
- ^ POTENTIAL STROBING AT THIS LEVEL
- MIN LOSES DIMMABILITY BELOW THIS LEVEL
- MAX MAXIMUM LUMENS OUTPUT

	2 BULBS						5 BULBS						30 BULBS					
	MIN	20	40	60	80	MAX	MIN	20	40	60	80	MAX	MIN	20	40	60	80	MAX
LUTRON SUNNATA STCL-153PH-WH-C	^	✓	✓	✓	✓	•	✓	✓	✓	✓	✓	•	✓	✓	✓	✓	✓	•
LUTRON MAESTRO MACL-153MH	^	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	^	✓	✓	✓	✓
LUTRON DIVA® / DIVA® C.L DVWCL-153PH			MIN	✓	✓	✓			MIN	✓	✓	✓			MIN	✓	✓	✓
LEVITON DECORA SURESLIDE®	✓	✓	✓	✓	✓	✓	^	✓	✓	✓	✓	✓		^	✓	✓	✓	✓
LUTRON C.L SKYLARK CONTOUR CTL -153P		MIN	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
LUTRON CASETA® WIRELESS	✓	✓	✓	✓	✓	✓	•	✓	✓	✓	✓	✓	•	✓	✓	✓	✓	✓
LEVITON DECORA ROCKER SLIDE	✓	✓	✓	✓	✓	✓	•	✓	✓	✓	✓	^	•	•	✓	✓	✓	^
LEVITON DECORA SMART™	✓	✓	✓	✓	✓	✓	•	✓	✓	✓	✓	✓	✓	•	✓	✓	✓	✓
LUTRON MAESTRO PRO MA-PRO-WH	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓